

**PROPOSED CONSTRUCTION OF ARANYA BHAWAN ANNEX  
- AT PANJABARI, GUWAHATI - 781 037.**

**BOQ OF COMPOUND DRAIN**

Sl.	Specification of item of works	Unit	Qty	Rate	Amount
	<b>EARTHWORK IN EXCAVATION</b>				
1	Earthwork in excavation for foundation trenches of walls, retaining walls, footings of column, steps, septic tank etc. including refilling (return filling) the quantity as necessary after completion of work, breaking clods in return filling, dressing, watering and ramming etc. and removal of surplus earth with all lead and lifts as directed and specified in the following classification of soils including bailing out water where necessary as directed and specified.				
	(A) Up to a depth of 2.00m below the existing ground level.	Cu.M.	88.00		
	(a) In ordinary soil				
	<b>PLAIN CEMENT CONCRETE WORKS</b>				
2	Plain cement concrete works with coarse aggregate of sizes 13mm to 32mm in foundation bed for footing steps, walls, brick works etc. as directed and specified including dewatering if necessary, and curing complete (shuttering where necessary shall be measured and paid separately).	Cu.M.	15.00		
	(a) In prop 1cement: 3 sand :6 coarse aggregate by volume				
	<b>MASONRY WORKS</b>				
3	Providing <b>soling</b> in foundation and under floor with stone/ best quality picked jhama brick, sand packed and laid to level and in panel after preparing the subgrade as directed including all labour and materials and if necessary dewatering, complete.	Sq.M.	147.00		
	(a).Brick on flat soling.				

Sl.	Specification of item of works	Unit	Qty	Rate	Amount
	<b>IN SUB-STRUCTURE.</b>				
4	Brick work in cement mortar with 1st class brick including racking out joints and dewatering if necessary, and curing complete as directed				
	(l) <b>In Sub-structure</b> up to plinth level.				
	(b). In proportion 1:4.	Cu.M.	22.50		
	<b>CEMENT PLASTERING</b>				
5	<b>15 mm thick Cement plaster in single coat on</b> rough side of single or half brick wall for interior plastering up to 1st floor level including arises, internal rounded angles, not exceeding 80mm girth and finished even and smooth including curing complete as directed.				
	<b>A) On rough side</b>				
	(b). In cement mortar 1:4	Sq.M.	304.00		
6	Neat Cement Punning	Sq.M.	304.00		
	<b>GRAND TOTAL RS</b>				